

Connector

MINI DIN JACK Series



KLS1-285A Mini din jack Without Shell Series

MATERIAL

Insulator: PBT UL 94V-0 or PPS
Shell: Brass, Nickel / Tin Plated or Tin Plated
Contact: Phosphor Bronze, Gold / Tin plated
ENVIRONMENTAL
Operating Temperature: -25°C ~ + 70°C

ELECTRICAL

Contact current Rating: 1 Amp/100VAC
2Amp/12VDC
Dielectric Withstanding: AC 1000V / min.
Insulation Resistance: 5000M OHM min AT 500V DC
Contact Resistance: 30m ohm Max.
Insertion force: 4.5Kgf Max
Withdrawal Force: 0.8Kgf Min
Life: 5000 cycles



ARRANGEMENT OF CONTACTS			
NO. OF CONTACTS	3	4	5
PCB LAYOUT			
ARRANGEMENT OF CONTACTS			
NO. OF CONTACTS	6	7	8
PCB LAYOUT			

ORDER INFORMATION

Product NO.: KLS1 - 285A - 4 B

Pos. NO. _____
Mini DIN JACK Without Shell Series _____
Pin Number: _____
3=3P 4=4P 5=5P 6=6P 7=7P 8=8P
Color: B=Black G=Green _____